

Kubota



KUBOTA DIESEL TRACTOR

B2530 – New from Kubota – 18kw tractor.



Available with Cab or Open Station & ROPS.

Fully Independent Rear & Mid PTO.

Features Kubota's unique Bi-Speed Turn for an exceptionally tight turning circle.



New HST

The HST models now have three range shift speeds, so the operator can more easily find the optimum working speed. In addition, the HST offers greater torque, making it easy to drive—and work—on slopes, or low implements.



Mechanical Cruise Control

Boasting 8 speeds to choose from, the multi-stage cruise control allows the operator to effortlessly set, increase/decrease, and override pre-set speeds (press the HST pedal) without resetting the cruise control lever. It's especially handy when working on large areas or moving the tractor between locations.



Fully Hydrostatic Power Steering

To make driving the tractor as effortless as possible, Kubota utilises hydrostatic power steering, allowing the operator to smoothly steer the tractor with ease.



Universal Design

The control lever guides are angled to provide increased visibility and simpler operation, and the levers themselves are large and easy to handle.

Specifications

PTO Power:		14kw
Engine:	Make:	Kubota
	Type	Indirect Injection, Water cooled, 4 cycle Diesel
	No of cylinders:	3
	Displacement:	1123cc
	Gross Power (SAE)	18.4 kw @ 2700 RPM
	Max Torque:	72 N-M
Capacities:	Fuel Tank:	27 litres
Dimensions:	Overall length:	2430mm (w/o 3p hitch)
	Overall width:	1105mm
	Overall height:	2290 (ROPS)
		2090 (Cab)
	Min ground Clearance:	285mm
	Turning Radius:	2.1m
Weight:	ROPS:	750kg
	Cab:	960kg
Tyres:	Front:	6.00-12
	Rear:	9.5-18
Steering:		Hydraulic Power steering
Transmission:	Main:	Continuously Variable Hydrostatic
	Range:	3 gears
Brakes:		Wet Disc
Hydraulics:	Pump capacity:	20.5 litres/min
	3 Pt lift:	Cat I
	Max Lift:	970kg at lift ends
		760kg 600mm behind lift ends
PTO:	Rear:	540 RPM
	Mid:	2500 RPM
Speeds:	Forward:	23km/h
	Reverse:	18km/h