

AJ-401-LH

Plus



WIDE SWATH SPRAYING



AJ-401-LH

Plus

- Sprays up to 30 meters downwind with outstanding coverage.
- Has a cover at the cannon opening to protect the nozzles during transport.
- Its auxiliary rotary atomizer ensures ideal spray swath
- Allows low and ultralow volume applications.
- It is easy to operate and to adjust vertically and horizontally.
- It can be used on various crops: cotton, flowers, cereals, livestock, vegetables and tobacco.
- Modern, low cost and little maintenance.



TANK
Made of high density polyethylene, a material that resists well impacts and sun rays. Has a easy to read level indicator.



PUMP AND FILLING VALVE

- Pump: centrifugal, robust and easy to access for maintenance.
- Filling valve: can fill the tank in 5 minutes only, without changing the sprayer calibration.



IN-LINE FILTER
It protects the nozzles from impurities and abrasive particles of chemicals.



CONTROL VALVE
It is located within the tractor driver's reach. Easy to increase or decrease the application rate.

TECHNICAL SPECIFICATIONS

Weight	230 kg
Tank	400 liters
Pump	Capacity: 120 l/min
Filter	Min.: 1,00 l/ha Max.: 430 l/ha
Fan	Rotation: 3,630 rpm Air speed: 232 km/h
Working speed	from 2 to 6 km/h

JACTO: THE NAME MEANS QUALITY



MÁQUINAS AGRÍCOLAS JACTO S.A.

Rua Dr. Luiz Miranda, 1650 - 17580-000 - Pompéia - SP - Brazil

Tel.: +55 14 3405 2100 - Fax: +55 14 3452 1306

E-mail: export@jacto.com.br

www.jacto.com.br