



KUBOTA 4WD COMPACT TRACTOR

B1610

ReDesigned For Improved Ease-Of-Use,
The Best-Selling Compact Is Even Better

Featuring an all-new design for enhanced ergonomics, extra comfort and increased safety.

Getting behind the wheel of a new Kubota B1610 is easier than ever. With all levers relocated to the side, the flat deck now offers easier, unrestricted access, more leg room and greater simplicity of operation. You'll find comfort in reduced levels of noise and vibration — especially at the end of a long day. Also, as the muffler is totally enclosed, your visibility is enhanced for easier front implement operation.

Two Power Take-Offs

The 2-speed rear PTO gives you exceptional flexibility with a variety of implements. The mid-PTO also features power for the heavy-duty, low-noise 48" mid-mount mower.

Side Selection Operation

All levers have been repositioned to the side to allow not only greater leg room but also simplified and more accessible tractor operation.

Kubota Diesel

One of the hardest-working engines in Kubota's history, the smooth-running 3-cylinder, 16 PS, liquid-cooled diesel, with Kubota's E-TVCS (three-vortex combustion system) delivers tremendous power and high torque with cleaner emissions.

New Full-Open Hood

B1610 feature a tilt-up hood with removable side covers and front grille, for easy servicing and maintenance.



Hydraulic 3-Point Hitch

The Cat.I 3-point hitch is designed to handle a variety of implements with fast and easy hook-up. Its hydraulic system functions smoothly and provides positive action.

Semi-Flat Deck

For abundant leg room and unimpeded foot space, a semi-flat deck design has been incorporated. As well, a rubber mat and rubber-padded foot pedals provide an extra measure of comfort and safety.

Beveled Four-Wheel-Drive

With power supplied to all four wheels, the tractor can move steadily and easily over wet and sandy ground. When extra traction is not needed, the 4WD is easily disengaged.

Specifications

Model		B1610		
Engine	Make	Kubota		
	Type	E-TVCS, indirect injection, vertical, liquid cooled, 4 cycle diesel		
	DIN power	kW (PS)	10.7 (14.5)	
	SAE power	kW (HP)	11.7 (16.0)	
	PTO power	kW (PS)	9.2 (12.5)	
	No. of cylinders	3		
	Total displacement	cm ³	719	
	Muffler	Fully enclosed		
	Air cleaner	Fully enclosed, dry paper element		
	Fuel tank	ℓ (imp·gal)	13 (2.86)	
Drive train	Driving method	4WD		
	Transmission speed	F6R2		
	max. travelling speed	km/h (mph)	with standard farm tyre 16.2 (10.1)	
	Brake type	Wet disc		
PTO	PTO type	Transmission driven with one way clutch		
	Rear PTO speed	rpm	540 /1000	
	Mid PTO speed	rpm	2545	
Hydraulic system				
	Pump capacity	ℓ/min (imp·gpm)	14.1 (3.1)	
	Lift capacity (lower link)	kg (N, lbs.)	540 (5292, 1190)	
	Hydraulic circuit changeover unit	Standard		
Dimensions	Overall length (w/o 3P)	mm (in.)	2035 (80.1)	
	Overall width (min tread)	mm (in.)	with standard farm tyre 927 (36.5)	
	Overall height (steering)	mm (in.)	1255 (49.4)	
	Wheelbase	mm (in.)	1270 (50)	
	Ground clearance	mm (in.)	270 (10.6)	
	Tread (front)	mm (in.)	with standard farm tyre 767 (30.2)	
	Tread (rear)	mm (in.)	711-1031 (28.0-40.6)	
	Weight*	kg (lbs.)	522 (1151)	
	Tyre	Farm	front	5-12
			rear	8-16
		Turf	front	20 × 8.00-10
			rear	212 / 80D-15
	Turning radius (with 4WD brake)	m (in.)	1.8 (70.9)	
Other	Steering	Manual		
	Water temp. gauge	Standard		
	Fuel gauge	Standard		
	Tachometer	Standard		
	Tool	Standard		
	Tool Box	Standard		
	Operator deck	Semi flat		
	Mower cutting width	mm (in.)	1219 (48)*	

The company reserves the right to change the above specifications without notice.

*Manufacture's estimate.

**Specifications may vary among markets.

*Mower deck can not attach tractor with farm tyre 5-12, 8-16.



KUBOTA Corporation

Head Office: 2-47, Shikitsuhashi 1-chome, Naniwa-ku, Osaka, Japan
Telex KUBOTA J65251 Fax (06) 6648-3521

Tokyo Office: 1-3, Nihonbashi-Muromachi 3-chome, Chuo-ku, Tokyo, Japan
Telex 222-3681 KUBOTA J