



# CONDOR 800 M-12

Robustness, Economy  
and High Yield.



# High Quality Components Ensuring the Equipment Durability

| TECHINICAL SPECIFICATIONS                         | Condor 800 M-12                             |
|---|---|
| Weight  | 363 kg                                      |
| <b>Dimensions</b>                                 |   |
| Lenght  | 1,10 m                                      |
| Height  | 3,40 m                                      |
| Width   | 1,60 m                                      |
| <b>Tank</b>                                       |   |
| Capacity  | 800 liters                                  |
| Material  | Polyethylene                                |
| Level indicator                                   | Hose attached to the tank                   |
| Clean water tank in polyethylene                  | 30 liters                                   |
| <b>Booms</b>                                      |   |
| Lenght  | 12 meters with actuation through winches    |
| Minimum spraying height                           | 0,50 m                                      |
| Maximum spraying height                           | 1,30 m                                      |
| <b>Nozzle Holder</b>                              |   |
| Model   | Monojet or Bijet                            |
| Nozzle spacing                                    | 0,35 or 0,50 m                              |
| Quantity  | 33 (0,35m) or 24 (0,50m)                    |
| Nozzle fitted                                     | JA-2 / UF-02                                |
| <b>Pump</b>                                       |   |
| Model   | JP-75 or JP-100                             |
| Flow rate at 540 rpm                              | 75 L/min or 100 L/min                       |
| Maximum working pressure                          | 300 psi                                     |
| <b>Pressure Gauge</b>                             | Extended scale with glycerin                |
| <b>Spray Control</b>                              |   |
| VAR   | 2 or 4 ways                                 |
| Masterflow  | 2 or 4 ways                                 |
| <b>Chemical Mixer with Container Rinse Nozzle</b> | 23-liter capacity                           |
| <b>Chemical Agitation</b>                         | Hydraulic or mechanic                       |
| <b>Filter</b>                                     | FVS-100 - 60 mesh                           |
| <b>In-Line Filter (optional)</b>                  | 2 or 4 (according to the control) - 80 mesh |
| <b>Filter Unit</b>                                | AFL-75 or AFL-100                           |
| <b>Row Marker</b>                                 | Mastermark                                  |
| <b>Recommended Working Speed</b>                  | Up to 6 km/h                                |

Imageexpress

Jacto reserves the right to change its products without prior notice. 10/2004. Always read the operator's manual before operating the equipment.



Jacto people are committed to serve the farmer.

Rua Dr. Luiz Miranda, 1650 - 17580-000 - Pompéia - SP - Brazil- Tel.: +55 14 3405 2100 - Fax.: +55 14 3452 1306 - E-mail: export@jacto.com.br

[www.jacto.com.br](http://www.jacto.com.br)