



KUBOTA DIESEL FRONT MOWER

F

# F2880/F3680

Two high-performance professional out front mowers perfect for a wide range of commercial applications. Both feature power, traction, and versatility, for outstanding productivity.



# Powerful out front mowers with the productivity and durability you need for professional mowing jobs.

Whatever your mowing application, there's a Kubota F-Series mower that can do the job with power, precision, and efficiency. These are hard-working professional mowers designed for tough commercial applications like yours. Both offer powerful Kubota diesel engines, more durable, fabricated mower decks, exceptional mowing performance, and superior operator comfort. They promise to bring a new level of productivity and reliability to all your mowing needs.





#### **Kubota Diesel Engines**

Powerful Kubota diesel engines mean faster, more efficient job performance. These F-Series diesel engines have power to spare. Their high torque rise ensures faster, smoother recovery under sudden loading, letting you power through tall or wet grass without skipping a beat. They're also environmentally and economically friendly, thanks to their enhanced combustion efficiency, low vibration and noise levels, and reduced fuel costs.

F2880 28HP/3000RPM F3680 36HP/3000RPM

# HIGH-PERFORMANCE

From powerful engines to increased lifting capacity, the F-Series has what it takes to get more work done in less time.









#### **Increased lifting capacity**

#### Tilt-wheel power steering

#### 4WD and Auto-Assist 4WD Large capacity fuel tank

A 40% increase in lifting capacity gives the F-Series the versatility to handle a variety of front implements.


Hydrostatic power steering reduces operator fatigue and makes it easier to mow around trees and other obstacles. The tilt steering wheel can be quickly adjusted for optimum operator comfort.

Auto-Assist 4WD works in forward and reverse, automatically controlling the drive loads on the wheels during turns. Auto-Assist 4WD lets you turn with greater efficiency and ease with less wear and tear to the turf. Full-time 4WD can also be engaged.

A larger, 61-litre fuel tank not only keeps you working longer between fuel stops, it also reduces the number of fuelling stops needed to complete long jobs. That means more time working and less time fuelling up.



A durable, hard-working deck that's ready for a wide range of mowing jobs.









# Fabricated deck with 7-gauge steel construction

Stronger and more durable than conventional pressed steel decks, the F-Series' fabricated steel deck is designed to provide years of reliable cutting performance with minimal maintenance.

#### 5.5" deep mower deck

Tall grass is no problem for this professional mower deck. Its 5.5"-deep deck design lets tall grass stand up so that it can be cut more efficiently. The result? A faster cut and a cleaner appearance.

#### PTO shaft drive

Shaft drive means no belts or pulleys – just smooth and direct power transfer from the engine to the deck and other PTO-driven attachments. Shaft drive also requires less maintenance and provides greater dependability.

#### Multi-V-belt/Steel pulleys

In addition to providing greater wear resistance, the heavy-duty cast-iron pulleys and multi-V-belt drive system effectively distribute and reduce tension while transmitting power to the mower blades. The multi-V-belt won't twist or slip, thus reducing the chance of damage to the mower. You get more performance and power – and fewer problems.

# 2. Rear Discharge

Made with 7-gauge steel, our rear discharge mower offers an alternative to our side deck. As with our side discharge mower, two sizes – 60" and 72" – are available. This deck features front lift arms that attach directly over the centre of gravity for better control.

## 3. Mulching (with optional mulching kit)

The professional mulching kit converts the deck into a highprecision mulching deck that produces an even finer mulch and sends it straight back into the turf. Mulching kits are available for both side discharge and rear discharge decks.









A durable and hard-working deck that's ready for a wide range of mowing jobs.









#### **Dual-element air cleaner**

The dual-element air cleaner helps keep the engine running smoothly and efficiently. Only the outer filter needs to be replaced-the inner filter can be cleaned with a blower-helping to reduce maintenance costs. The F3680 air cleaner is equipped with a choke indicator that turns red when the filter needs cleaning or replacement.

#### Integrated radiator screen Electric fuel gauge

The new, easy to clean radiator screen is integrated into the engine cover to help the engine run cooler and more efficiently. A water temperature gauge and overheating alarm are also provided to help prevent overheating.

No more guessing how much fuel remains in the tank. An electric fuel gauge makes fuel level monitoring as easy as a quick glance at the front panel.

#### **Tool box**

Conveniently located under the seat, the tool box provides fastaccess storage for your tools. It's also an ideal place to store your operator manual for quick and easy reference while on the job.

#### Single HST Pedal

A more powerful hydrostatic transmission provides quicker response, increased working speed, and more muscle for tough mowing jobs. The single pedal design lets you easily change the direction as well as control the speed (20 km/h max. forward speed, 11 km/h in reverse). This keeps your hands free during steering and implement control for

increased productivity.



The all-important key to safe, efficient, productive mower operation.



#### Halogen headlight

The bright halogen headlight throws more light onto the work area, letting you work with greater efficiency and speed in low-light and nighttime situations. An optional working light is also available.



#### Larger tyres with wider tread

The four tyres are larger and have more tread, providing greater stability and maneuverability on slopes, better flotation and less ground compaction.





#### **Deluxe seat**

The F-Series' high level of comfort starts with a deluxe high-back seat with four separate adjustments-weight control, lumbar support, back angle, and arm rests-to provide every operator with a custom fit and optimum comfort.

#### **Operator levers**

For easier operation and greater convenience, the High/Low speed lever, deck lifting lever, and PTO Start/Stop lever have been lengthened and moved to the side of the operator's seat. The lever guides have also been redesigned for quick, at-a-glance identification.



#### **Specifications**

Model			F2880	F3680		
			4WD			
Engine						
Model			Kubota D1105	Kubota V1505		
Туре			Liquid-cooled diesel (3 cyl)	Liquid-cooled diesel (4 cyl)		
Max. horsepower		HP	28	36		
Total displacement cm <sup>3</sup>		cm <sup>3</sup>	1,123 1,498			
Air cleaner	Type		Dual elemen	t		
	Air restriction indicator		N/A	Standard		
Alternator		12 V, 40A				
Fuel tank capacity		$\ell$	61.0			
Transmission Type			HST (F2/R2)			
Max. travel speed	Forward / Reverse km/h (mph)		20 (12.5)/11 (6.8)			
4WD mode select		. , ,	Auto-assist 4WD with dual acting overrunning clutch/locked 4WD			
Differential lock			Standard Standard			
Cruise control			Optional			
Tyre						
Front			24×12-12			
Rear			18×9.5-8			
Brake			Wet discs			
Steering						
Туре			Hydrostatic power			
Tilt steering			Standard			
Dimension						
Tread (F/R)		mm (in.)	1063 (41.8)/1045 (41.1)			
Wheel base		mm (in.)	1,300 (52.0)			
Overall length mm (in.)		2,500 (100.0)				
Overall width		mm (in.)	1,370 (54.8)			
Overall height (w/o ROPS) mm (in.)		mm (in.)	1,350 (54.0)			
Weight (w/o ROPS)		kg (lbs.)	727 (1603) 744 (1640)			
Ground clearance		mm (in.)	185 (7.4)			
Mower mounting Type			Independent live, Sh	aft drive		
PTO revolution			2,545			
Clutch			Wet multi discs, hydraulic			
Lift system			Hydraulic 2-point hitch			
Tilt angle		Degrees	90			
Weight transfer			Standard			
Others						
Fuel gauge			Electric mete	r		
Tachometer			Optional			
Toolbox			Standard			
Seat			Reclining suspension seat			
Cup holder			Standard			
ROPS			Optional			

### **Mower Specifications**

Model		RCK60-F36	RCK72-F36	RCK60R-F36	RCK72R-F36	
Discharge		Side discharge		Rear discharge		
Cutting width mm (in.)		1,520 (60)	1,826 (72)	1,520 (60)	1,826 (72)	
Cutting height	mm (in.)	25 (1) -127 (5)				
Cutting height adjustment	mm (in.)	Each 6.4 (0.25)				
Depth	mm (in.)	140 (5.5)				
Deck pan		Welded				
Thickness	mm (in.)	4.5 (0.18)				
Number of blades		3				
Tilt assist		N/A	Standard	N/A	Standard	
Turn assist brake		N/A	Standard	N/A	Standard	
Mulch kit		Optional				

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty and safety information.

For your safety, KUBOTA strongly recommends the use of a Roll Over Protective Structure (ROPS) and seat belt in almost all applications.



**KUBOTA (U.K.) LIMITED** 

©2005 Kubota Corporation