

All Falcon equipment is designed to be simple, safe and serviceable, offering excellent value for money. Excellent customer service is also part of the Falcon promise. Our equipment is built to last and is capable of coping with tough South African conditions.

Product Groups and Products

Slashers

Light Duty
Medium Duty
Heavy Duty
Extra Heavy Duty

Haymaking Equipment

Haymakers[®]
Bale Handling Equipment
Unloaders[™]

Spreaders

Rotorspreaders
Limespreaders

Ground Engaging Equipment

Rotavators (and Bedformers)
Ploughs

Mowers

Blowermowers[™]
Grassmulchers[™]
Rollermowers
Rotagangs[™]

Mulchers

Fieldmulchers[™]
Side Discharge Mulchers

Imported Product Range

Falcon Agricultural Equipment imports and distributes the following range of products:

Slashers

Woods Batwing BW1800 4.5 m
Woods Batwing BW3240 6 m

Mowers

Votex Flail Mowers
Votex Reach Mowers
Amazone Groundkeepers

Spreaders

Amazone Spreaders

Shredders

Votex Shredders



BALE HANDLING EQUIPMENT

The Falcon range of bale handling equipment can collect, transport, load, unload and stack various sizes of bales. Bales of 750 kg can be lifted to a height of 3,4 m.



Tel: +27 (0)33 330 4764
Fax: +27 (0)33 330 2120
E-mail: info@falconequipment.co.za
www.falconequipment.co.za

FALCON F750 UNILOADER[™]



Stacking big pack Lucerne bales

The Falcon F750 Uniloader[™] loads and stacks both round and square bales and can take on other general lifting and loading jobs. Depending on which tractor is used, the F750 Uniloader[™] can lift up to 750 kg to a height of 3,4 m.

The unique design also allows the F750 Uniloader[™] to transport bales in the field.



Stacking round bales

The mast is simply lowered to rest on the support brackets, and the tractor linkage then raises the loader so that the bale is clear of the ground.

The ability of the F750 Uniloader[™] to lift loads of up to 750 kg and to a height of 3,4 m means that it is capable of loading bales two high on a trailer or stacking them three to five high on the ground, depending on their size.



Can be used for other loading jobs

The standard two-spool valve fitted to most modern tractors operates the lifting and levelling cylinders. However, the necessary operating valves can be supplied for older tractors.



Quick and easy to hitch onto the tractor

The F750 Uniloader[™] is fitted with telescopic legs and can be parked free-standing and ready to be easily hitched to the tractor when required.

FALCON BALE FORK



Falcon Bale Fork

The Bale Fork is a low-cost implement for the in-field loading of hay bales (max. 750 kg) and their transportation to the bale storage area.

FALCON BALE FORK LOADER



Falcon Bale Fork Loader

The Bale Fork Loader is used to stack hay bales (max. 500 kg) in the storage area. The maximum lift height to the centre of the bale is 2,7 m, and varies depending on the tractor size.

Important Note: Please do not use the Bale Fork Loader as a transporter as this will damage the loader causing early failure. Rather, the Bale Fork should be separated from the loader and used to transport the bales.

Alle Falcon-toerusting is ontwerp om eenvoudig, veilig en diensbaar te wees en uitstekende waarde vir geld te bied. Voortreflike klantediens is ook deel van die Falcon-belofte. Ons toerusting is gebou om te hou en is in staat om die strawwe Suid-Afrikaanse toestande die hoof te bied.

Produkroepe en Produkte

Wentelsnyers

Ligtediens
Mediumdiens
Swaardiens
Ekstraswaardiens

Hooimaaktoerusting

Haymakers[®]
Baalhanteringtoerusting
Uniloaders[™]

Strooiers

Misstrooiers
Kalkstrooiers

Grondbewerkingstoerusting

Rotavators (en Saadbedvormers)
Ploeë

Grassnyers

Blowermowers[™]
Grassmulchers[™]
Rollersnyers
Rotagangs[™]

Mulchers

Fieldmulchers[™]
Side Discharge Mulchers

Ingevoerde Produkreeks

Die volgende produkreeks word deur Falcon Agricultural Equipment ingevoer en versprei:

Wentelsnyers

Woods Batwing BW1800 4.5 m
Woods Batwing BW3240 6 m

Grassnyers

Votex-swaaiemsniers
Votex-reiksniers
Amazone Groundkeepers

Strooiers

Amazone Strooiers

Stokkiekappers

Votex-stokkiekappers



BAALHANTERING-TOERUSTING

Falcon se reeks baalhanteringtoerusting kan verskeie groottes bale optel, vervoer, laai, aflai en op mekaar stapel. Bale van 750 kg kan tot 'n hoogte van 3,4 m opgelig word.



Tel: +27 (0)33 330 4764
Faks: +27 (0)33 330 2120
E-pos: info@falconequipment.co.za
www.falconequipment.co.za

FALCON F750 UNILOADER[™]



Stapel van grootpak-lusernbaale

Die Falcon F750 Uniloader[™] laai en stapel sowel ronde as vierkantige bale en kan ook vir ander algemene oplig- en laaitake gebruik word. Na gelang van die trekker wat

gebruik word, kan die F750 Uniloader[™] tot 750 kg tot 'n hoogte van 3,4 m oplig.

Die unieke ontwerp maak dit ook moontlik vir die F750



Stapel van ronde bale

Uniloader[™] om bale in die veld te vervoer. Die mas word eenvoudig laat sak om op die steunarms te rus, en die trekkerkoppelmeganisme lig dan die F750 Uniloader[™] sodat die baal bo die grond is.

Die F750 Uniloader[™] se vermoë om vragte van tot 750 kg tot 'n hoogte van 3,4 m op te tel, beteken dit kan twee bale bo-op mekaar op 'n sleepwa laai en drie tot vyf bale bo-op mekaar op die grond stapel, na gelang van hulle grootte.



Kan vir ander laaiwerk gebruik word

Die standaard tweespoelklep aan die meeste moderne trekkers beheer die oplig- en kantelsilinders. Die nodige beheerkleppe



Haak vinnig en maklik aan die trekker

kan egter vir ouer trekkers voorsien word. Die F750 Uniloader[™] is toegerus met teleskopiese pote en kan vrystaande geparkeer word, gereed om, wanneer nodig, maklik aan die trekker gehaak te word.

FALCON-BAALVURK



Falcon-baalvurk

Die Baalvurk is 'n lae-koste-impliment om hooibale (maks. 750 kg) in die veld te laai en hulle na die baalbergingsgebied te vervoer.

FALCON-BAALVURKLAAIER



Falcon-baalvurklaaier

Die Baalvurklaaier word gebruik om hooibale (maks. 500 kg) in die bergingsgebied te stapel. Maksimum lighoogte na die middel van die bale is 2,7 m, en wissel na gelang van trektergrootte.

Belangrik: Moet asseblief nie die Baalvurklaaier gebruik om bale te vervoer nie – dit sal die laaier beskadig en vroeë onklaarraking veroorsaak. Skei die Baalvurk eers van die laaier en gebruik dit dan om die bale te vervoer.